


M-THERMO 16 T

16-channel thermocouple inputs type T (Cu/CuNi)

- 4 PT100 for cold junction compensation
- Status LED at each measurement channel
- Measurement data output to CAN
- Galvanic isolation (inputs, CAN, supply, enclosure)
- Designed for engine compartment applications
- Toolless module to module connection
- Ruggedized and compact modules for harsh environments



Device	
Maximum input protection voltage (channel)	±50 V (indefinitely), ±200 V (short-time, t < 2 ms)
Channel sampling rates	1/ 2/ 5/ 10/ min – 1/ 2/ 5/ 10/ 20 Hz
Aggregate sample rate	320 Hz
Voltage supply	9 ... 36 VDC
Supply voltage thresholds	Ein 9 ±0.3 VDC / Aus 6 ±0.3 VDC
Power consumption, typical	1.2 W
Working temperature range	-40 ... 125 °C (-40 ... 257 °F)
Storage temperature range	-55 ... 150 °C (-67 ... 302 °F)
IP-Code	IP 67 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	W204 mm x H41 mm x D55 mm (8.03 in x 1.61 in x 2.17 in)
Weight	630 g (0.69 lb)
Configuration interface	CAN high speed
Data transfer rate	Software selectable up to 1 Mbit/s (ISO11898-2)
Input sockets	Miniature TC connector brown (DIN IEC 584)
Input sockets	Miniature TC connector blue (ANSI MC 96.1)
Galvanic isolation	
Input module power supply	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input CAN	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input enclosure	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input input	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
General channel properties	
A/D converter	16 bit / SAR (successive approximation register)
Sensor break detection	Activation via software settings
Channel LED	Available
Flashing mode of channel LED	Break detection - permanent active

Flashing mode of channel LED	During configuration - blinking
Channel impedance	10 M Ω (inactive sensor break detection)
Channel impedance	1 M Ω (active sensor break detection)
Hardware filter (fixed)	1 Hz, filter type RC-low-pass
Channel temperature	
Measurement range temperature	Type T (Cu/CuNi) -60 ... 400 °C (-76 ... 752 °F)
Accuracy at ambient temperature 25 °C	± 0.15 % in the range -60 ... 400 °C (-76 ... 752 °F)
Drift for ambient temperature 85 ... 120 °C	± 40 ppm/K
Drift for ambient temperature -40 ... 85 °C	± 40 ppm/K
Linearization of sensor characteristic line	Numerical interpolated
Cold junction compensation (CJC)	4 PT100 (1 for 4 channels)
Accessories	
System cable	620-561.pdf
System cable	620-502.pdf
System cable	620-560.pdf
System cable	620-567.pdf
System cable	620-509.pdf