

8-channel thermocouple measurement inputs type K (NiCr/NiAl)

- 1 PT100 for cold junction compensation in multi pin socket
- Measurement data output to CAN
- Galvanic isolation (inputs, CAN, supply, enclosure)
- Designed for engine compartment applications
- Toolless module to module connection
- Ruggedized and compact modules for harsh environments



Device	
Maximum input protection voltage (channel)	±50 V (indefinitely), ±200 V (short-time, t < 2 ms)
Channel sampling rates	1/ 2/ 5/ 10/ min – 1/ 2/ 5/ 10/ 20 Hz
Aggregate sample rate	160 Hz
Voltage supply	9 ... 36 VDC
Supply voltage thresholds	Ein 9 ±0.3 VDC / Aus 6 ±0.3 VDC
Power consumption, typical	1.1 W
Working temperature range	-40 ... 125 °C (-40 ... 257 °F)
Storage temperature range	-55 ... 150 °C (-67 ... 302 °F)
IP-Code	IP 67 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	W118 mm x H32 mm x D46 mm (4.65 in x 1.26 in x 1.81 in)
Weight	218 g (0.48 lb)
Configuration interface	CAN high speed
Data transfer rate	Software selectable up to 1 Mbit/s (ISO11898-2)
Input sockets	Multipol TC connector HGG 2 B 316 (NiCr/NiAl)
Galvanic isolation	
Input module power supply	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input CAN	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input enclosure	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
Input input	±100 V (indefinitely), ±200 V (short-time, t < 2 ms)
General channel properties	
A/D converter	16 bit / SAR (successive approximation register)
Sensor break detection	Activation via software settings
Channel LED	No
Channel impedance	10 MΩ (inactive sensor break detection)
Channel impedance	1 MΩ (active sensor break detection)

Hardware filter (fixed)	1 Hz, filter type RC-low-pass
Channel temperature	
Measurement range temperature	Type K (NiCr/NiAl) -60 ... 1370 °C (-76 ... 2498 °F)
Accuracy at ambient temperature 25 °C	±0.025 % ±3 K for full measurement range
Accuracy at ambient temperature 25 °C	±0.035 % in the range -60 ... 1000 °C (-76 ... 1832 °F)
Accuracy at ambient temperature 25 °C	±0.035 % ±3 K in the range 1000 ... 1370 °C (1832 ... 2498 °F)
Drift for ambient temperature 85 ... 120 °C	±30 ppm/K
Drift for ambient temperature -40 ... 85 °C	±20 ppm/K
Linearization of sensor characteristic line	Numerical interpolated
Cold junction compensation (CJC)	1 PT100 (inside multi-pin socket)
Accessories	
System cable	620-561.pdf
System cable	620-502.pdf
System cable	620-560.pdf
System cable	620-509.pdf
System cable	M-CAN-ABS.pdf
System cable	M-DEF-200.pdf
Input cable	625-511.pdf
Input cable	625-507.pdf